



## **PURPOSE**

To hold or clamp wireline / slickline at surface during fishing operations.

## **ASSEMBLY PARTS**

1. Top Plate
2. Bottom Plate
3. Insert
4. Allen Cap Screw
5. Flat Head Screw

## **APPLICATION**

The Round Line Clamp is used when there is a desire to lubricate broke Slickline / Wireline from the wellbore. The Round Line Clamp utilizes a 5/8" SR thread which will attach to the bottom of a standard tool string, which then may be drawn up inside the lubricator.

## **OPERATION**

Extract Allen Cap Screws from Top and Bottom plates so clamp be separated into two parts.

Ensure proper sized inserts are installed into clamp before installing around line.

Install around line, ensuring the slickline / wireline is aligned in the centre of the inserts. Install Allen Cap Screws into Top and Bottom plates and tighten, this will hold the line stationary.

*(Sizes on next page)*

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061

Nominal Size		Assembly Number	Insert
Item	Line Size		
1	0.092"	0501LCR231A0	0501LCR23104
2	0.108"	0501LCR231A2	0501LCF00005
3	0.125"	0501LCR231A3	0501LCF00006
4	0.140"	0501LCR231AA	0501LCF00007
5	0.150"	0501LCR231A3	0501LCF00008
6	0.160"	0501LCR231A4	0501LCF00009
7	0.187"	0501LCR231A5	0501LCF00010
8	0.218"	0501LCR231A6	0501LCF00011
9	0.250	0501LCR231A7	0501LCF00012
10	0.312"	0501LCR231A8	0501LCF00013
11	0.375"	0501LCR231A9	0501LCF00014
12	Top Plate	0501LCR23101	n/a
13	Bottom Plate	0501LCR23102	n/a
14	Allen Head Cap Screw	0.50" - 13 UNC x 1"	n/a
15	Flat Head Screw	10-24 x 0.50"	n/a
Upper Thread Connection		0.938 - 10 UN	n/a

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061