



PURPOSE

A means of attaching larger slickline to the Wireline Tool String.

ASSEMBLY PARTS

1. Body
2. Slip Carrier
3. Slip
4. Bottom Sub
5. Set Screw

APPLICATIONS

Designed for use with larger diameter slickline 0.140" and larger. The Slip Type Rope Socket utilizes a pair of slips in conjunction with a taper to grip the slickline and hold it in place during slickline operations.

PRECAUTIONS

Care should be taken to ensure that the slips are not worn or damaged, also ensure that the slips are installed correctly with the etched arrow pointing in the upward direction, improper installation of the slips could lead to failure.

Nominal Size		1.50"	1.75"
Assembly Number		0101RSS150A0	0101RSS175A0
Item	Part Name		
1	Body	0101RSS15001	0101RSS17501
2	Slip Carrier	0101RSS15002	0101RSS15002
3	Slip	0101RSS15003	0101RSS15003
4	Retainer Sub	0101RSS15004	0101RSS17504
5	Set Screw	.375" UNC x .25"	.375" UNC x .25"
Lower Thread Connection		0.938"-10 UN	1.062"-10 UN
Max O.D.		1.50"	1.75"
Fishneck size		1.37"	1.75"

1. toolstring equipment

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061