



PURPOSE

The Halliburton style CXN Profile Nipple is a non-selective type nipple that is placed at the bottom of the tubing string. The CXN is a non-selective type profile nipple which means it cannot be ran in conjunction with other CXN nipples of the same size, as the plugging equipment cannot pass through the no-go or restriction in the bottom of the nipple.

The CXN Profile Nipple typically comes with EUE box x pin thread connections, but is not limited to this; special or premium connections are available upon request as well as a wide range of materials for adverse well conditions.

Halliburton Type CXN							
Tubing O.D.		Seal Bore		No-Go I.D.		Min O.D.	
IN	MM	IN	MM	IN	MM	IN	MM
1.900"	48.26	1.500"	38.10	1.448"	36.78	2.13	54.10
2.063"	53.37	1.625"	41.28	1.536"	39.01	2.62	66.54
2.375"	60.33	1.875"	47.63	1.791"	45.29	2.73	69.34
2.875"	73.02	2.313"	58.75	2.666"	56.00	3.25	82.47
3.500"	88.90	2.750"	69.85	2.635"	66.93	3.77	95.66
3.500"	88.90	2.81"	71.45	2.666"	68.53	3.77	95.66
4.500"	114.30	3.813"	96.85	3.725"	94.62	4.92	124.97

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061