



### PURPOSE

Setting in tubing strings without upsets, typically integral joint where couplings do not exist.

Used primarily for straddle pack offs, or tubing pack offs.

### ASSEMBLY PARTS

1. Fishneck
2. Slips
3. Retainer Wire

### DESCRIPTION

Internal fishing neck.

When setting, the tapered slip carrier forces the slips tight to the inner tubing wall.

Ran with a shear down pulling tool, G Running Tool, or a GS. Pulled with a GS or GR pulling tool.

### OPERATION

Attach to desired running tool and lower into wellbore to desired depth. Set slips by jarring tapered fishneck down and forcing slips against inner tubing wall, shear off and remove toolstring wellbore.

To retrieve the G Anchor, attach the GS/GR to toolstring and lower into wellbore, latch and jar up to release the slip from the taper, remove from wellbore.

Nominal Size		2.00"	2.50"	3.00"
Assembly Number		1002GA200A0	1002GA250A0	1002GA300A0
Item	Part Name			
1	Fishneck	1002GA20001	1002GA25001	1002GA30001
2	Slip	1002GA20002	1002GA25002	1002GA30002
3	Retainer Wire	1002GA20003	1002GA25003	1003GA30003
Wire Size		0.135" X 4.375"	0.135" X 5.75"	0.135" X 7.375"
Lower Thread Connection		1.625" - 12 UN	2.062" - 12 UN	2.50" - 12 UN
Max O.D.		2.00"	2.44"	3.00"
Min. O.D.		1.835"	2.28"	2.71"
Fishneck size		1.375"	1.81"	2.31"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061