



**PURPOSE**

To locate and retrieve Wireline from the wellbore.

**ASSEMBLY PARTS**

1. Fishneck
2. Mandrel
3. Top Sub
4. Body
5. Washer
6. Dart
7. Tapered Sleeve
8. Skirt (may come in different O.D.'s)

**OPERATION**

Attach to the toolstring and lower into wellbore. Once the top of the wire is found, work the Wire Retriever up and down to allow the wire to become trapped between the skirt and the tapered cone. Once this has been achieved, remove toolstring and broken wire from the wellbore.

**APPLICATIONS**

The Wire Retriever may be used when there is a desire to locate and potentially retrieve a broken (parted) slickline or wire.

Different size fingered skirts may be interchanged depending on the tubing size.

Nominal Size		2.00"
Assembly Number		0506WG200A0
Item	Part Name	
1	Fishneck	0506WG20001
2	Mandrel	0506WG20002
3	Top Sub	0506WG20003
4	Body	0506WG20004
5	Washer	0506WG20005
6	Dart	0506WG20006
7	Taper Sleeve	0506WG20007
8	Skirt - 1.86"	0506WG18608
9	Skirt - 2.25"	0506WG22808
10	Skirt - 2.70"	0506WG27008
Top Thread Connection		0.938"10 UN
Max O.D.		2.70"
Fishneck size		1.37"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061