



#### PURPOSE

To hold or clamp wireline / slickline at surface during fishing operations.

#### ASSEMBLY PARTS

1. Top Plate
2. Bottom Plate
3. Insert
4. Allen Cap Screw
5. Flat Head Screw

#### OPERATION

Extract Allen Cap Screws from Top and Bottom plates so clamp can be separated into two parts.

Ensure proper sized inserts are installed into clamp before installing around line.

Install around line, ensuring the slickline / wireline is aligned in the centre of the inserts. Install Allen Cap Screws into Top and Bottom Plates and tighten. This will hold the line stationary.

Nominal Size		Assembly Number	Insert
Item	Line Size		
1	0.092"	0501LCF000A0	0501LCF00004
2	0.108"	0501LCF000A2	0501LCF00005
3	0.125"	0501LCF000A3	0501LCF00006
4	0.140"	0501LCF000A4	0501LCF00007
5	0.150"	0501LCF000A5	0501LCF00008
6	0.160"	0501LCF000A6	0501LCF00009
7	0.187"	0501LCF000A7	0501LCF00010
8	0.218"	0501LCF000A8	0501LCF00011
9	0.250	0501LCF000AB	0501LCF00012
10	0.312"	0501LCF000A9	0501LCF00013
11	0.375"	0501LCF000AA	0501LCF00014
12	Top Plate	0501LCF00001	n/a
13	Bottom Plate	0501LCF00002	n/a
14	Allen Head Cap Screw	0.50" - 13 UNC x 2"	n/a
15	Flat Head Screw	10-24 x 0.375"	n/a

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061