



PURPOSE

Resizing inside diameters of downhole completion equipment.

DESCRIPTION

Broaching tools most commonly used are made up of one piece.

Solid circular body with a series of offset cutting pads or cutting rings surrounding the circumference of the entire body length.

The series of cutting edges diameters increase from the bottom to the top of the tool until reaching the maximum outside diameter on the top one or two series of cutting pads or rings of tool body.

The graduated diameters of cutting edges are usually in increments of .0001 of an inch in some cases they may increase by one half of .0001 of an inch.

Nominal Size	1.660"	1.900"	2.062"	2.00
Assembly Number	0101BT12801	0101BT15101	0101BT16501	0101BT19101
Fishneck OD	1.00"	1.187"	1.187"	1.375"
Pin Connection	0.62"-11 NC	0.938"-10 UN	0.938"-10 UN	0.938"-10 UN
Max OD	1.28"	1.513"	1.657"	1.906

Nominal Size	2.50"	3.00"	4.50"
Assembly Number	0101BT23401	0101BT286001	0101BT39601
Fishneck OD	1.375"	1.75"	2.313"
Pin Connection	0.938"-10 UN	1.062"-10 UN	1.062"-10 UN
Max OD	2.347	2.867"	3.965

Special Sizes Upon Request

1. toolstring equipment

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061