



PURPOSE

The Halliburton style CR Profile Nipple is a selective type nipple that may be placed anywhere in the tubing string. The CR is a selective type profile nipple which means it be ran in conjunction with other CR nipples of the same size, as the plugging equipment can pass through one and be set in another.

The CR Profile Nipple typically comes with EUE box x pin thread connections, but is not limited to this, special or premium connections are available upon request as well as a wide range of materials for adverse well conditions

The CR Profile Nipple is typically used in situations where pressure may exceed the limits of the X line equipment, or in conditions where size restriction require specific profile diameters.

Halliburton Style CR					
Tubing O.D.		Seal Bore		Min O.D.	
IN	MM	IN	MM	IN	MM
2.375"	60.33	1.71"	43.43	2.560"	65.02
2.375"	60.33	1.78"	45.24	2.560"	65.02
2.375"	60.33	1.875"	47.03	2.560"	65.02
2.875"	73.02	2.125"	53.98	3.109"	78.97
2.875"	73.02	2.188"	55.58	3.109"	78.97
2.875"	73.02	2.31"	58.75	3.109"	78.97
3.500"	88.90	2.56"	65.07	3.687"	93.65
3.500"	88.90	2.750"	69.85	3.687"	93.65
3.500"	88.90	2.81"	71.37		
4.500"	114.30	3.43"	87.30	5.200"	132.08
4.500"	114.30	3.68"	93.68	5.200"	132.08
4.500"	114.30	3.81"	96.85	5.200"	132.08

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061