



PURPOSE

Used to pressure test tubing.

ASSEMBLY PARTS

- 1. Mandrel
- 2. Equalizing Fishneck
- 3. Body
- 4. Bottom Nogo Sub

APPLICATION

Set in a PSN or profile nipple to check the integrity before or after the tubing is run.

OPERATION

Install the AW Test Plug in the desired nipple, this may be achieved by either wireline or by dropping the test plug and pumping it into place.

After pressure testing, lower the toolstring with a JUS/RS Pulling Tool into wellbore and latch the second fishneck of the AW Test Plug, jar up to shear the pin and slide fishneck up to expose equalizing ports. After the tubing string has been equalized, pull the AW Test Plug from sealbore and remove toolstring from the wellbore.

PRECAUTIONS

The AW Test Plug holds pressure from above only, Ensure that the no-go on the AW Test Plug corresponds to the nipple to be utilized.

Nominal Size		2.00"	2.50"
Assembly Number		1101TT200A0	1101TT250A0
Item	Part Name		
1	Mandrel	1101TT20001	1101TT20001
2	Equalizing Fishneck	1101TT20002	1101TT20002
3	Body	1101TT20003	1101TT25003
4	Bottom Sub	1101TT20004	1101TT25004
Max O.D.		1.91"	2.347"
Fishneck Size		1.37"	1.37"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061