



### PURPOSE

To manipulate the lock dogs on a BKO style selective style lock mandrel to allow dogs to collapse and assembly to be removed from a profile, or tubing collar.

The AC Probe allows upward facing lock dogs of a selective (type S) to be retracted if necessary.

### ASSEMBLY PARTS

1. Spindle
2. Retaining Head
3. Blade
4. Segments

### PRECAUTIONS

Ensure that the probe body does not get worn down to far to prevent lock dogs from retracting properly.

Rust, sand or debris in the swivel (spindle) will hamper tool operations.

Nominal Size		1.50"/2.062"	2.00"	2.50"
Assembly Number		0703AC150A0	0703AC200A0	0703AC250A0
Item	Part Name			
1	Spindle	0703AC15001	0703AC20001	0703AC20001
2	Retaining Head	0703AC15002	0703AC20002	0703AC25002
3	Blade	0703AC15003	0703AC20003	0703AC25003
4	Segments	0703AC15004	n/a	n/a
Upper Thread Connection		0.50"-13 UNC	0.50"-13 UNC	0.50"-13 UNC
Max O.D.		0.718"	0.827"	1.132"

Nominal Size		2.56"	3.00"	4.00"
Assembly Number		0703AC200A0	0703AC300A0	0703AC400A0
Item	Part Name			
1	Spindle	0703AC20001	0703AC30001	0703AC40001
2	Retaining Head	0703AC25602	0703AC30002	0703AC40002
3	Blade	0703AC25603	0703AC30003	0703AC40003
4	Segments		n/a	n/a
Upper Thread Connection		0.50"-13 UNC	0.625"-11 UNC	1.25"-12 UN
Max O.D.		1.174"	1.382"	2.31"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061