



PURPOSE

Used in conjunction with an A circulating mandrel to pressure test tubing.

ASSEMBLY PARTS

1. Packing Sub
2. No-Go Nut
3. Retainer Nut
4. Female Backup Ring
5. O-Ring

APPLICATION

Set in a PSN or profile nipple to check the integrity before or after the tubing is run.

OPERATION

Install the PSN test plug in the desired nipple, this may be achieved by either wireline or by dropping the test plug and pumping it into place.

After pressure testing, lower the toolstring with a jar up / jar down pulling tool into wellbore and latch the fishneck of the A Circulating Mandrel jar up to shear the pin and slide fishneck up to expose equalizing ports. After the tubing string has been equalized, pull the PSN test plug from sealbore and remove toolstring from the wellbore.

PRECAUTIONS

The PSN Test Plug holds pressure from above only, Ensure that the no-go on the test plug corresponds to the nipple to be utilized.

Nominal Size		2.00"	2.50"	3.00"
Assembly Number		1101PSN200A0	1101PSN250A0	1101PSN300A0
Item	Part Name			
1	Packing Sub	1101PSN20001	1101PSN25001	1101PSN30001
2	No-Go Nut	1101PSN20002	1101PSN25002	1101PSN30002
3	Retainer Nut	1101PSN20003	1101PSN25003	1101PSN30003
4	Female Backup Ring	0903BUR17801	0903BUR22801	0903BUR27501
5	O-Ring	219	222	222
Max O.D.		1.906"	2.347"	2.83"
Upper Thread Connection		1.187" - 14 UN	1.187" - 14 UN	1.187" - 14 UN

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061