



**PURPOSE**

To confirm that the R Locks have been set in the appropriate landing nipple.

**ASSEMBLY PARTS**

- 1. Fishneck
- 2. Core
- 3. Body

**OPERATION**

Install desired shear pin and attach to tool string, lower into wellbore. Set down on top of lock mandrel and jar down, remove toolstring from wellbore and inspect the R Check Set tool.

If the pin is sheared in the R Check Set, this will indicate that the lock mandrel is set correctly, if it is not sheared, this will indicate that the fishneck of the lock mandrel is not all the way down into the set position and should be dealt with accordingly.

*(Sizes on next page)*

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061

Nominal Size		1.78"	2.18"	2.75 - 2.81"	3.68"
Assembly Number		0202RCS178A0	0202RCS218A0	0202RCS275A0	0202RCS368A0
Item	Part Name				
1	Fishneck	0202XCS20001	0202XCS25001	0202RCS27501	0202RCS36801
2	Core	0202RCS17802	0202RCS21802	0202RCS27502	0202RCS36802
3	Body	0202XCS20003	0202XCS25003	0202RCS27503	
Top Thread Connection		0.938" - 10 UN	0.938" - 10 UN	1.062" - 10 UN	1.062" - 10 UN
Max O.D.		1.75"	2.16"	2.68"	3.65"
Fishneck size		1.375"	1.375"	1.75"	2.31"

\* Non-Stock Item. Please call for price and delivery.

2. running tools

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061

CANADA

•

USA

•

INTERNATIONAL

•

[www.bracetool.com](http://www.bracetool.com)