



**PURPOSE**

To cut slickline and / or wireline above the rope socket when necessary.

**ASSEMBLY PARTS**

1. Drop Bar (18")
2. Drop Bar (30")
3. Drop Bar (60")
4. Body
5. Cutter Block
6. Cutter Wheel
7. Plunger

**OPERATION**

Attach to the line using care to ensure all internal parts are aligned and the two halves of the cam cutter fit back together around line properly and pins are installed in drop bar. Allow cutter to slide down line until the rope socket is impacted, this will shear the pins, actuate the cutter wheel and snip the line.

Nominal Size		1.62"
Assembly Number		0501CC162A0
Item	Part Name	
1	Drop Bar (18")	0501CC16201
2	Drop Bar (30")	0501CC16202
3	Drop Bar (60")	0501CC16203
4	Body	0501CC16102
5	Cutter Block	0501CC20003
6	Cutter Wheel	0501CC16104
7	Plunger	0501CC16105
Top Thread Connection		1.062" - 10 UN
Max O.D.		1.62"
Fishneck size		1.375"
Max Line Size Cut		0.25"

\*Various size threaded guides for the drop bars are available upon request for use in larger size tubing and casing.

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061