



PURPOSE

Connects wireline surface equipment to wellhead.

DESCRIPTION

The lower end of the swage connection is either threaded or flanged to fit the wellhead. The upper end of the swage is compatible to the bottom hand union of the BOP.

Standard thread sizes of swage connections carried on slickline units are: 2 and 3 inch line pipe, 2 3/8, 2 7/8 and 3 1/2 inch EUE.

EUE threads have pressure ratings the same as that of standard wireline surface equipment.

Line Pipe

Nominal Size	2.00"	3.00"
Assembly Number	1306S20002	1306S30002
Top Thread Connection	4.75" - 4 ACME	4.75" - 4 ACME
Lower Thread Connection	2.00" Line Pipe	3.00" Line Pipe
Max O.D.	4.75"	4.75"

EUE

Nominal Size	2.375	2.875"
Assembly Number	1306S20001	1306S25001
Top Thread Connection	4.75" - 4 ACME	4.75" - 4 ACME
Lower Thread Connection	2.375" EUE - 8RD	2.875" EUE - 8 RD
Max O.D.	4.75"	4.75"

Nominal Size	3.50"	2.875"
Assembly Number	1306S3001	1306S30003
Top Thread Connection	4.75" - 4 ACME	4.75" - 4 ACME
Lower Thread Connection	3.50" EUE - 8RD	4.50" EUE - 8 RD
Max O.D.	4.75"	4.75"

Casing

Nominal Size	4.50"	5.50"
Assembly Number	1306S30004	1306S30005
Top Thread Connection	4.75" - 4 ACME	4.75" - 4 ACME
Lower Thread Connection	4.50" LTC - 8RD	5.50" LTC - 8 RD
Max O.D.	4.75"	5.50"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061