

**PURPOSE**

To retrieve subsurface tools, used typically during fishing operations.

ASSEMBLY PARTS

1. Fishneck
2. Skirt

OPERATION

Select proper size of fingered overshot and attach to the tools string, lower into wellbore.

Once desired fish has been located, jar down to latch fishneck and begin jarring operations

PRECAUTIONS

The Fingered Overshot does not contain a shearing mechanism, if the ability to shear is desired, a pulling tool may be run above the Fingered Overshot, or the Collet Pulling Tool may be used.

(Sizes on next page)

Nominal Size		0.68"	0.75"	1.00"	1.18"
Assembly Number		0501FO068A0	0501FO075A0	0501FO100A0	0501FO118A0
Item	Part Name				
1	Fishneck	0501FO06801	0501FO07501	0501FO10001	0501FO11801
2	Skirt	0501FO06802	0501FO07502	0501FO10002	0501FO11802
Max O.D.		0.875"	1.00"	1.25"	1.61"
Fishneck size latched		0.68"	0.75"	1.00"	1.18"
Fishneck size		0.75"	.075"	1.00"	1.18"

Nominal Size		1.375"	1.75"	2.31"
Assembly Number		0501FO137A0	0501FO175A0	0501FO231A0
Item	Part Name			
1	Fishneck	0501FO13701	0501FO17501	0501FO23101
2	Skirt	0501FO13702	0501FO17502	0501FO23102
Max O.D.		1.77"	2.125"	2.688"
Fishneck size latched		1.375"	1.75"	2.31"
Fishneck size		1.375"	1.75"	1.75"



When ordering please specify part name and size. Call us toll free: 1-800-438-0061