



#### **PURPOSE**

The No-Go Dart is intended to be landed either in or on a profile nipple or tubing swedge to act as a platform to land sub surface instruments on.

#### **APPLICATIONS**

The No-Go Dart comes in several different designs, ranging from a gauge ring style dart with an integral fishneck, to a fluted style dart with threaded connections.

#### **PRECAUTIONS**

Ensure that the No-Go Dart is the proper size before attempting to land in desired profile nipple, failure to do this may result in lost or damaged equipment.

*(Sizes continue on next page)*

12. bhp equipment

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061

## Gauge Ring No-Go Darts

Nominal Size	1.50"	1.75"	2.00"	2.50"	3.00"
Assembly Number	1201DGR15001	1201DGR17501	1201DGR20001	1201DGR25001	1201DGR30001
Max O.D.	1.51"	1.656"	1.91"	2.347"	2.867"
Fishneck size	1.18"	1.18"	1.37"	1.37"	1.75"

## Fluted No-Go Darts - Threaded

Nominal Size	2.00"	2.50"	3.00"
Assembly Number	1201DF20002	1201DF25002	1201DF30002
Top Thread Connection	0.938"-10 UN	0.938"-10 UN	0.938"-10 UN
Lower Thread Connection	0.938"-10 UN	0.938"-10 UN	0.938"-10 UN
Max O.D.	1.91"	2.347"	2.867"
Fishneck size	1.37"	1.37"	1.37"

## Fluted No-Go Darts - Non-Threaded

Nominal Size	2.00"	2.50"	3.00"
Assembly Number	1201DF20001	1201DF25001	1201DF30001
Lower Thread Connection	0.938"-10 UN	0.938"-10 UN	0.938"-10 UN
Max O.D.	1.91"	2.347"	2.867"
Fishneck size	1.37"	1.37"	1.37"

When ordering please specify part name and size. Call us Toll Free: 1-800-438-0061